

## Nano Glassfibre LED Tube

- Lighter than you think.
- Does not shatter.
- Easier to install & safer than glass tube.



Model NO.	Rated Power	Lumen Output	Rated Voltage	Frequency	CCT	CRI	Beam Angle	Dimensions
T8-1500M	10W	1500Lm	200-240Vac	50/60Hz	3000-6000K	>80	180	28×1198mm
T8-1800M	12W	1800Lm	200-240Vac	50/60Hz	3000-6000K	>80	180	28×1198mm
T8-2100M	14W	2100Lm	200-240Vac	50/60Hz	3000-6000K	>80	180	28×1198mm
T8-2400M	16W	2400Lm	200-240Vac	50/60Hz	3000-6000K	>80	180	28×1198mm
T8-2600M	18W	2600Lm	200-240Vac	50/60Hz	3000-6000K	>80	180	28×1198mm
T8-09-110D	9W	1500Lm	200-240Vac	50/60Hz	3000-6000K	>80	110	28×1198mm
T8-11-110D	11W	1800Lm	200-240Vac	50/60Hz	3000-6000K	>80	110	28×1198mm
T8-13-110D	13W	2100Lm	200-240Vac	50/60Hz	3000-6000K	>80	110	28×1198mm
T8-15-110D	15W	2400Lm	200-240Vac	50/60Hz	3000-6000K	>80	110	28×1198mm
T8-17-110D	17W	2600Lm	200-240Vac	50/60Hz	3000-6000K	>80	110	28×1198mm
T8-09-110D600	9W	1200Lm	200-240Vac	50/60Hz	3000-6000K	>80	110	28×598mm
T8-09-110D1500	18W	2700Lm	200-240Vac	50/60Hz	3000-6000K	>80	110	28×1498mm